

4x3D

4x3D Radio Mount Instructions

Thank you for choosing a custom 4x3D Radio Mount! Follow these instructions to get the most out of your mount.

Installation Instructions

1. Attach the Mount:
2. Secure the mount to your desired surface using the two screw holes (55mm centers). For flat surfaces, use appropriate screws or bolts.
3. Optional Strap Installation:
4. For roll bars or rounded surfaces, thread the Velcro straps through the 20mm side slots. Ensure the mount is tight and secure.
5. Ball Adapter Setup:
6. Attach the 20mm or 1-inch ball adapter to the center mounting hole using the provided M5-8 button head bolt.
7. Snap in Your Radio:
8. Align your radio with the mount and press it into place until you feel a secure click.

Handheld Microphone Holder

If you purchased the optional Handheld Microphone Holder, follow these steps:

1. Align the microphone holder with the two mounting holes on your radio mount (55mm centers).
2. Attach the holder using the provided screws, ensuring the mount is secure.
3. Mount the microphone on either the left or right side of the holder for flexibility.

Note: The microphone holder cannot be used with Velcro straps, as it occupies the same slots for a more secure connection.

Enjoy the **Journey!**

Thank you for choosing **4x3D**. We hope you new mounts in your Jeep.

